

# KX-T7885 KX-T7885-W 900MHz Multi-Line Wireless Telephone



- 12 CO Line Capability
- 3-Line Multi-Function LCD Readout
- Caller ID Compatible\*
- Headset Jack & Belt Clip
- Message Waiting Indicator
- Vibrating or Ringer Signal

**900MHz**  
WIRELESS




**Panasonic**  
ideas for life

# KX-T7885 900MHz Multi-Line Wireless Telephone

## Outstanding Features with Built-In Quality

### 900MHz

Provides clear sound, enhanced range and reduced interference from radios, computer monitors and fluorescent lighting compared to ordinary wireless phones.



### Flexible Keys for up to 12 CO Lines

The portable handset features 4 flexible keys with 3 positions each. In PBX mode, these keys can be programmed to access a total of up to 12 CO (central office) lines, system features or a combination of both. In SLT mode, they can be used to store 12 telephone numbers for convenient one-touch dialing.

### Caller ID Compatible\*

When integrated with a Panasonic Digital Super IP-PBX Hybrid or Advanced Hybrid phone system, the KX-T7885 can display an incoming caller's phone number or name for effective call screening.

### 6 Ringer Modes

The KX-T7885 features 6 different ringer modes with a step ringer that gradually increases in volume. The vibrator ring is perfect for use in situations when an audible ring would not be desirable.

### 3-Line Multi-Function LCD Readout

Provides helpful information like Caller ID data\*, call information, line status, and flexible key number or name.

### Hands-Free Headset Jack

Now there's no need to interrupt your workflow just to answer the phone. You can connect an optional hands-free headset to the KX-T7885 for automatic answering of intercom calls, plus access to features like BGM and Paging.

### Combination Buttons

By pressing the FUNC key and one of the assigned numerical keys, you can access certain features including Pause, Conference, Call Forward, DND and Flash.

### Wall-Mountable Base Antenna

You can keep the handset cradle on your desk and position the base antenna in a location that is central to your workspace, enabling you to maximize your range within that space.

### Handset Cradle/Spare Battery Charger\*\*

Allows you to charge a spare battery\*\*\* while using another in the handset.

### 12 One-Touch and 10 Auto-Dial Numbers\*\*\*\*

Allows you to store up to 12 phone numbers for one-touch dialing. You can also store 10 additional numbers for convenient speed dialing. Each phone number can be up to 24 digits in length, enabling you to include access codes.

## High Capacity, Quick-Charging NiMH Battery

### Handy Belt Clip

### Message Waiting Indicator

### 30-Channel Auto Scanning

### Handset Locator

### Sound Charger™ Noise Reduction Technology

### FWD, DND, Redial, Transfer and Hold Keys

### Available in Black or White

\* PBX mode only. Requires the installation of an optional Caller ID Card in the host PBX System. Also requires a subscription to Caller ID service offered by certain telephone companies for a fee. \*\*Spare battery not included. \*\*\*KX-A276 and KX-A276-W spare battery can be purchased separately. \*\*\*\*SLT Mode only.

## KX-T7885 Specifications

Base Unit	
Power Source:	AC Adapter
Duplex Frequency Bands:	902.125 - 927.600 MHz
Specific Channel Numbers:	30
Adjacent Channel Rejection:	60 dB
Sensitivity:	1.0uV for 15 dB
Dial Mode:	Tone (DTMF)/Pulse
ID Code:	20-bit
Dimensions (HxWxD):	1-5/8" x 4-3/4" x 6-13/16"
Weight:	0.70 lb. (315 g)
Charging Unit	
Power Source:	AC Adapter
Dimensions (HxWxD):	4-5/8" x 3-3/8" x 2-5/16"
Weight:	0.33 lb. (150 g)
Portable Handset Unit	
Duplex Frequency Bands:	902.125 - 927.600 MHz
Specific Channel Numbers:	30
Adjacent Channel Rejection:	60 dB
Sensitivity:	1.0 uV for 15dB
Speed Dial Memory Capacity:	12 One-Touch (F1 - F12), 20 Digits Each****, 10 Auto-Dial (Feature Code Access), 20 Digits Each****
Redial:	Up to 30 Digits
Pause:	3.5 Seconds
Flash:	700 ms
ID Code:	20-bit
Power Source:	NiMH Battery
Charging Time:	1.5 Hours
Talk Time:	Up to 4 Hours
Standby Time:	3 Days
Dimensions (HxWxD):	7-9/16" x 1-15/16" x 1-3/16"
Weight:	0.42 lb. (191 g)

## Panasonic ideas for life

### Panasonic Consumer Electronics Company

Division of Matsushita Electric Corporation of America  
Executive Offices: One Panasonic Way, Secaucus, NJ 07094  
(201) 348-7000  
www.panasonic.com

### Panasonic Sales Company (Puerto Rico)

Division of Matsushita Electric of Puerto Rico, Inc.  
San Gabriel Industrial Park, Ave. 65 de Infanteria,  
Km. 9.5, Carolina, PR 00984  
(787) 750-4300

### Panasonic Customer Service

9am - 9pm (EST) Monday through Friday  
10am - 7pm (EST) Saturday and Sunday  
1-800-211-PANA  
consumerproducts@panasonic.com

Design and specifications subject to change without notice.